

Ceiling Speaker



Ceiling Speaker					
Model	CSK-36C	CSK-36E	CSK-46E	CSK-33B	CSK-36B
Description	3" Ceiling Speaker	3" Ceiling Speaker	4" Ceiling Speaker	3" Ceiling Speaker	3" Waterproof Ceiling Speaker
Rated Power Output	1.5W-3W-6W	1.5W-3W-6W	1.5W-3W-6W	1.5W-3W	1.5W-3W-6W
Line Input	100V or 70V	100V or 70V	100V or 70V	100V or 70V	100V or 70V
Frequency Response	120-20KHz	120-20KHz	90-18KHz	80-20KHz	150-18KHz
SPL(@1W/m)	87dB	87dB	90dB	91dB	91dB
Speaker Unit	3 full range paper cone	3" full range paper cone	4" full range paper cone	3" full range paper cone	3" full range waterproof cone
Cutout Size	95mm	90mm	112mm	99mm	125mm
Dimension	103(D)×80(H)mm	101(D)×60(H)mm	135(D)×85(H)mm	121(D)×96(H)mm	140(D)×130(H)mm
Material	ABS enclosure and metal grille in white	Metal enclosure and metal grille in white	Metal enclosure and metal grille in white	ABS enclosure, ABS back cover and metal grille in white	ABS enclosure, ABS back cover and metal grille in white
Mounting Way	In-ceiling spring clip quick installation	In-ceiling spring clip quick installation	In-ceiling spring clip quick installation	In-ceiling spring clip quick installation	In-ceiling spring clip quick installation
Weight	0.4kg	0.4kg	0.65kg	0.41kg	0.9kg

Ceiling Speaker				
Model	CSK-56E	CSK-66E	CSK-56M	CSK-66M
Description	5" Ceiling Speaker	6" Ceiling Speaker	5" Ceiling Speaker	6" Ceiling Speaker
Rated Power Output	1.5W-3W-6W	1.5W-3W-6W	1.5W-3W-6W	1.5W-3W-6W
Line Input	100V or 70V	100V or 70V	100V or 70V	100V or 70V
Frequency Response	100-15KHz	100-15KHz	110-13KHz	100-18KHz
SPL(@1W/m)	93dB	93dB	88dB	92dB
Speaker Unit	5 full range paper cone	6" full range paper cone	5" full range paper cone	6" full range paper cone
Dimension	175(D)×60(H)mm	188(D)×76(H)mm	165mm	175mm
Cutout Size	150mm	170mm	197(D)×60(H)mm	200(D)×65(H)mm
Material	ABS enclosure and metal grille in white	ABS enclosure and metal grille in white	Metal enclosure and metal grille in white	Metal enclosure and metal grille in white
Mounting Way	In-ceiling spring clip quick installation	In-ceiling spring clip quick installation	In-ceiling spring clip quick installation	In-ceiling spring clip quick installation
Weight	0.5kg	0.7kg	0.8kg	0.65kg

Ceiling Speaker					
Model	CSK-56P	CSK-56T	CSK-66T	CSK-56MC	CSK-66MC
Description	Ceiling Speaker with Cover	5" Waterproof Ceiling Speaker	6" Ceiling Speaker	5" Ceiling Speaker	6" Ceiling Speaker
Rated Power Output	3W-6W	3W-6W	3W-6W	1.5W-3W-6W	1.5W-3W-6W
Line Input	100V or 70V	100V or 70V	100V or 70V	100V or 70V	100V or 70V
Frequency Response	110-13KHz	150-12KHz	110-13KHz	110-13KHz	100-18KHz
SPL(@1W/m)	88dB	88dB	88dB	88dB	92dB
Speaker Unit	5" full range paper cone	5" full range PP waterproof woofer	6" full range paper woofer	5" full range paper cone	6" full range paper cone
Cutout	158mm	138mm	160mm	165mm	175mm
Dimension	190(D)×80(H)mm	172(D)×115(H)mm	198(D)×104(H)mm	197(D)×98(H)mm	200(D)×90(H)mm
Material	ABS enclosure, metal grille in white and ABS back cover in black	ABS enclosure, ABS grille in white and ABS back cover in white	ABS enclosure, ABS grille in white and ABS back cover in white	Metal enclosure, metal grille and metal back cover in white	Metal enclosure, metal grille and metal back cover in white
Mounting Way	In-ceiling spring clip quick installation	In-ceiling spring clip quick installation	In-ceiling spring clip quick installation	In-ceiling spring clip quick installation	In-ceiling spring clip quick installation
Weight	0.6kg	0.73kg	0.6kg	0.91kg	0.9kg

Ceiling Speaker



Ceiling Speaker			
Model	CSK-56X	CSK-610X	CSK-815X
Description	5" Dual Cone Ceiling Speaker	6" Dual Cone Ceiling Speaker	8" Dual Cone Ceiling Speaker
Rated Power Output	1.5W-3W-6W	3W-5W-10W	5W-10W-15W
Line Input	100V or 70V	100V or 70V	100V or 70V
Frequency Response	110-18KHz	110-18KHz	50-18KHz
SPL(@1W/m)	92dB	92dB	92dB
Speaker Unit	5" paper dual cone	6" paper dual cone	8" paper dual cone
Cutout Size	168mm	195mm	248mm
Dimension	203(D)×85(H)mm	230(D)×85(H)mm	280(D)×100(H)mm
Material	ABS enclosure and metal grille in white	ABS enclosure and metal grille in white	ABS enclosure and metal grille in white
Mounting Way	Flush mount in-ceiling quick and secure installation	Flush mount in-ceiling quick and secure installation	Flush mount in-ceiling quick and secure installation
Weight	0.7kg	0.9kg	1.3kg

Ceiling Speaker			
Model	CSK-56Q	CSK-610Q	CSK-815Q
Description	5" Coaxial Ceiling Speaker	6" Coaxial Ceiling Speaker	8" Coaxial Ceiling Speaker
Rated Power Output	1.5W-3W-6W	3W-5W-10W	5W-10W-15W
Line Input	100V or 70V	100V or 70V	100V or 70V
Frequency Response	110-20KHz	110-20KHz	50-20KHz
SPL(@1W/m)	93dB	93dB	93dB
Speaker Unit	5"+1.5" Coaxial Paper	6"+1.5" Coaxial Paper	8"+1.5" Coaxial Paper
Cutout Size	168mm	195mm	248mm
Dimension	203(D)×85(H)mm	230(D)×85(H)mm	280(D)×100(H)mm
Material	ABS enclosure and metal grille in white	ABS enclosure and metal grille in white	ABS enclosure and metal grille in white
Mounting Way	Flush mount in-ceiling quick and secure installation	Flush mount in-ceiling quick and secure installation	Flush mount in-ceiling quick and secure installation
Weight	0.7kg	0.9kg	1.3kg

Ceiling Speaker			
Model	CSK-520T	CSK-630T	CSK-840T
Description	5" Coaxial Ceiling Speaker	6" Coaxial Ceiling Speaker	8" Coaxial Ceiling Speaker
Rated Power Output	5W-10W-20W	10W-20W-30W	10W-20W-40W
Line Input	100V or 70V	100V or 70V	100V or 70V
Frequency Response	100-20KHz	100-20KHz	50-20KHz
SPL(@1W/m)	88dB	88dB	88dB
Speaker Unit	5" coaxial PP driver unit	6" coaxial PP driver unit	8" coaxial PP driver unit
Cutout Size	170mm	200mm	240mm
Dimension	203(D)×80(H)mm	230(D)×90(H)mm	270(D)×105(H)mm
Material	ABS enclosure and metal grille in white	ABS enclosure and metal grille in white	ABS enclosure and metal grille in white
Mounting Way	Flush mount in-ceiling quick and secure installation	Flush mount in-ceiling quick and secure installation	Flush mount in-ceiling quick and secure installation
Weight	1.25kg	1.6kg	2.1kg

- Voice Evacuation
- Class-D Amplifier
- Mixer Amplifier
- Power Amplifier
- 100V Speaker
- IP Network Audio
- IP Intercom
- PA System
- Microphone
- Conference System
- Mixing Console
- Pre Amplifier